

Standardy użycia silników – dwie prędkości

| Typ wciągnika | Cięgna nośne | Typ silnika (prędkość V1) | Ilość, szt. | Moc [kW] | I, A | Obroty nominalne [1/min] | Typ silnika (prędkość V2) | Ilość, szt. | Moc [kW] | I, A | Obroty nominalne [1/min] |
|---------------------|--------------|---------------------------|-------------|----------|-----------|--------------------------|---------------------------|-------------|----------|-----------|--------------------------|
| MT303, MT304, MT305 | 2/1, 4/1 | CT112M-12/4-240Tp1 | 1 | 0,83/2,5 | 5,8/6 | 430/1400 | CT112M-12/4-240Tp1 | 1 | 0,83/2,5 | 5,8/6 | 430/1400 |
| MT306, MT308 | 2/1, 4/1 | CT112M-12/4-240Tp1 | 1 | 0,83/2,5 | 5,8/6 | 430/1400 | CT132MA-12/4-240Tp1 | 1 | 1,33/4 | 7,6/9 | 450/1400 |
| MT310, MT312 | 2/1, 4/1 | CT132MA-12/4-240Tp1 | 1 | 1,33/4 | 7,6/9 | 450/1400 | CT132MB-12/4-240-6Tp1 | 1 | 2/6 | 10/13 | 440/1400 |
| MT313, MT316 | 2/1, 4/1 | CT132MB-12/4-240-5Tp1 | 1 | 1,66/5 | 8,4/10,8 | 460/1430 | MB132M-12/4 FDB20 Th A1 | 1 | 2,3/7 | 14,7/17,5 | 440/1440 |
| MT520, MT525 | 2/1, 4/1 | MB160MB-12/4 FDB20 Th A2 | 1 | 2,6/8 | 14,5/17,7 | 435/1440 | MB160LB-12/4 FDB23 Th A2 | 1 | 3,9/11,8 | 29/29,7 | 465/1465 |
| M732, M740 | 2/1, 4/1 | MB160LB-12/4 FDB23 Th A3 | 1 | 3,9/11,8 | 29/29,7 | 465/1465 | K3518A-24/4 Tp1 | 1 | 3,7/22 | 48/71 | 210/1400 |
| M750 | 2/1, 4/1 | K3517A-24/6 Tp1 | 1 | 3/13 | 30/40 | 220/960 | MB180L-12/4 FDB26 Th B14 | 1 | 5,3/16 | 29,7/36,5 | 475/1485 |
| M940, M950, M963 | 2/1, 4/1 | K3517-24/6 Tp1 | 1 | 3/13 | 30/40 | 220/960 | K3518-24/4 Tp1 | 1 | 3,7/22 | 48/71 | 210/1400 |
| *M980, M1100, M1125 | 2/1, 4/1 | K3518-24/6 Tp1 | 1 | 4/16 | 36/70 | 210/950 | K3518-24/4 Tp1 | 1 | 3,7/22 | 48/71 | 210/1400 |

Standardy użycia silników – jedna prędkość

| Typ wciągnika | Cięgna nośne | Typ silnika (prędkość V1) | Ilość, szt. | Moc [kW] | I, A | Obroty nominalne [1/min] | Typ silnika (prędkość V2) | Ilość, szt. | Moc [kW] | I, A | Obroty nominalne [1/min] |
|---------------------|--------------|---------------------------|-------------|----------|------|--------------------------|---------------------------|-------------|----------|------|--------------------------|
| MT303, MT304, MT305 | 2/1, 4/1 | CT100LA-4-240Tp1 | 1 | 2,5 | 5,4 | 1410 | CT100LA-4-240Tp1 | 1 | 2,5 | 5,4 | 1410 |
| MT306, MT308 | 2/1, 4/1 | CT100LA-4-240Tp1 | 1 | 2,5 | 5,4 | 1410 | CT112M-4-240Tp1 | 1 | 4 | 9,1 | 1420 |
| MT310, MT312 | 2/1, 4/1 | CT112M-4-240Tp1 | 1 | 4 | 9,1 | 1420 | CT132S-4-240-6Tp1 | 1 | 6 | 11,7 | 1440 |
| MT313, MT316 | 2/1, 4/1 | CT132S-4-240-5Tp1 | 1 | 5 | 11,5 | 1440 | MT132M-4 FDB20 Th A1 | 1 | 7 | 15,9 | 1420 |
| MT520, MT525 | 2/1, 4/1 | MT160MB-4 FDB20 Th A2 | 1 | 8 | 16,8 | 1430 | MT160LB-4 FDB23 Th A2 | 1 | 12 | 24 | 1425 |
| M732, M740 | 2/1, 4/1 | MT160LB-4 FDB23 Th A3 | 1 | 12 | 24 | 1425 | MT180L-4 FDB26 Th B14 | 1 | 18 | 38,1 | 1470 |
| M750 | 2/1, 4/1 | K2714A-6 Tp1 | 1 | 12,5 | 36 | 920 | MT160L-4 FDB23 Th A3 | 1 | 16 | 34,9 | 1476 |
| M940, M950, M963 | 2/1, 4/1 | K2714-6 Tp1 | 1 | 12,5 | 36 | 920 | K3518-4 Tp1 | 1 | 30 | 49 | 1400 |
| *M980, M1100, M1125 | 2/1, 4/1 | K3517-6 Tp1 | 1 | 22 | 42 | 950 | MT180L-4 FDB26 Th B14 | 1 | 24 | 50,1 | 1470 |

Standardy użycia silników – normalna zabudowa

| Typ wciągnika | Cięgna nośne | Numer | Typ silnika (dwie prędkości) | Ilość, szt. | Moc [kW] | I, A | Obroty nominalne [1/min] | Typ silnika (jedna prędkość) | Ilość, szt. | Moc [kW] | I, A | Obroty nominalne [1/min] |
|---------------------|--------------|-------|------------------------------|-------------|-----------|---------|--------------------------|------------------------------|-------------|----------|------|--------------------------|
| MT303, MT304, MT305 | 2/1 | 1 | KT80A-12/4 BR-35 | 1 | 0,08/0,25 | 1,2/1,3 | 450/1440 | KT63B-6 BR-35 | 1 | 0,12 | 0,63 | 880 |
| | 2/1 | 2 | T80B-12/4 BR-42 | 1 | 0,12/0,37 | 1,5/1,8 | 450/1440 | KT63B-6 BR-35 | 1 | 0,12 | 0,63 | 880 |
| | 4/1 | 1 | KT80B-12/4 BR-35 | 1 | 0,12/0,37 | 1,5/1,8 | 450/1440 | KT71B-6 BR-35 | 1 | 0,25 | 1,0 | 880 |
| | 4/1 | 2 | T80B-12/4 BR-42 | 1 | 0,12/0,37 | 1,5/1,8 | 450/1440 | KT71B-6 BR-35 | 1 | 0,25 | 1,0 | 880 |
| MT306, MT308 | 2/1 | 1 | KT80B-12/4 BR-35 | 1 | 0,12/0,37 | 1,5/1,8 | 450/1440 | KT71B-6 BR-35 | 1 | 0,25 | 1,0 | 880 |
| | 2/1 | 2 | T80B-12/4 BR-42 | 1 | 0,12/0,37 | 1,5/1,8 | 450/1440 | KT71B-6 BR-35 | 1 | 0,25 | 1,0 | 880 |
| | 4/1 | 1 | KT80B-12/4 BR-35 | 1 | 0,12/0,37 | 1,5/1,8 | 450/1440 | KT80A-6 BR-35 | 1 | 0,37 | 1,4 | 925 |
| | 4/1 | 2 | T80B-12/4 BR-42 | 1 | 0,12/0,37 | 1,5/1,8 | 450/1440 | KT80A-6 BR-35 | 1 | 0,37 | 1,4 | 925 |
| MT310, MT312 | 2/1 | 1 | KT80B-12/4 BR-35 | 1 | 0,12/0,37 | 1,5/1,8 | 450/1440 | KT80A-6 BR-35 | 1 | 0,37 | 1,4 | 925 |
| | 2/1 | 2 | T80B-12/4 BR-42 | 1 | 0,12/0,37 | 1,5/1,8 | 450/1440 | KT80A-6 BR-35 | 1 | 0,37 | 1,4 | 925 |
| | 4/1 | 1 | KT80B-12/4 BR-35 | 1 | 0,12/0,37 | 1,5/1,8 | 450/1440 | KT80A-6 BR-35 | 1 | 0,37 | 1,4 | 925 |
| | 4/1 | 2 | T80B-12/4 BR-42 | 1 | 0,12/0,37 | 1,5/1,8 | 450/1440 | KT80A-6 BR-35 | 1 | 0,37 | 1,4 | 925 |
| MT313, MT316 | 2/1 | 1 | KT80B-12/4 BR-35 | 1 | 0,12/0,37 | 1,5/1,8 | 450/1440 | KT80A-6 BR-35 | 1 | 0,37 | 1,4 | 925 |
| | 2/1 | 2 | T80B-12/4 BR-42 | 1 | 0,12/0,37 | 1,5/1,8 | 450/1440 | T80A-4 BR-42 | 1 | 0,55 | 1,75 | 1400 |
| | 4/1 | 1 | KT80B-12/4 BR-35 | 1 | 0,12/0,37 | 1,5/1,8 | 450/1440 | KT80A-6 BR-35 | 1 | 0,55 | 2,1 | 890 |
| | 4/1 | 2 | T90S-12/4 BR-42 | 1 | 0,18/0,55 | 1,7/1,2 | 450/1440 | T80A-4 BR-42 | 1 | 0,55 | 1,75 | 1400 |
| MT520, MT525 | 2/1 | 1 | KT80B-12/4 BR-35 | 1 | 0,12/0,37 | 1,5/1,8 | 450/1440 | KT80A-6 BR-35 | 1 | 0,55 | 2,1 | 890 |
| | 2/1 | 2 | T80B-12/4 BR-42 | 1 | 0,12/0,37 | 1,2/1,2 | 450/1440 | T80A-4 BR-42 | 1 | 0,55 | 1,75 | 1400 |
| | 4/1 | – | T90S-12/4 BR-42 | 2 | 0,18/0,55 | 1,7/1,2 | 450/1440 | T80A-4 BR-42 | 2 | 0,55 | 1,75 | 1400 |
| M732, M740 | 2/1 | – | T80B-12/4 BR-42 | 2 | 0,12/0,37 | 1,2/1,2 | 450/1440 | T80A-4 BR-42 | 2 | 0,55 | 1,75 | 1400 |
| | 4/1 | – | KT90S-8/2 | 2 | 0,18/0,75 | 1,4/1,9 | 680/2800 | KT80A-2 | 2 | 0,75 | 2,0 | 2820 |
| M750 | 2/1 | – | T90S-12/4 BR-42 | 2 | 0,18/0,55 | 1,7/1,2 | 450/1440 | T80A-4 BR-42 | 2 | 0,55 | 1,75 | 1400 |

Standardy użycia silników – niska zabudowa

| Typ wciągnika | Cięgna nośne | Typ silnika (dwie prędkości) | Ilość, szt. | Moc [kW] | I, A | Obroty nominalne [1/min] | Typ silnika (jedna prędkość) | Ilość, szt. | Moc [kW] | I, A | Obroty nominalne [1/min] |
|---------------------|--------------|------------------------------|-------------|-----------|-----------|--------------------------|------------------------------|-------------|----------|------|--------------------------|
| MT303, MT304, MT305 | 2/1 | KT71B-8/2 | 2 | 0,06/0,24 | 0,71/0,78 | 690/2820 | KT63B-2 | 2 | 0,25 | 0,68 | 2770 |
| | 4/1 | KT71B-8/2 | 2 | 0,06/0,24 | 0,71/0,78 | 690/2820 | KT63B-2 | 2 | 0,25 | 0,68 | 2770 |
| MT306, MT308 | 2/1 | KT71B-8/2 | 2 | 0,06/0,24 | 0,71/0,78 | 690/2820 | KT63B-2 | 2 | 0,25 | 0,68 | 2770 |
| | 4/1 | KT71B-8/2 | 2 | 0,06/0,24 | 0,71/0,78 | 690/2820 | KT63B-2 | 2 | 0,25 | 0,68 | 2770 |
| MT310, MT312 | 2/1 | KT71B-8/2 | 2 | 0,06/0,24 | 0,71/0,78 | 690/2820 | KT63B-2 | 2 | 0,25 | 0,68 | 2770 |
| | 4/1 | KT80B-8/2-53 | 2 | 0,13/0,55 | 1,4/1,6 | 710/2890 | KT71B-2-53 | 2 | 0,55 | 1,4 | 2790 |
| MT313, MT316 | 2/1 | KT71B-8/2 | 2 | 0,06/0,24 | 0,71/0,78 | 690/2820 | KT63B-2 | 2 | 0,25 | 0,68 | 2770 |
| | 4/1 | KT80B-8/2-53 | 2 | 0,13/0,55 | 1,4/1,6 | 710/2890 | KT71B-2-53 | 2 | 0,55 | 1,4 | 2790 |
| MT520, MT525 | 2/1 | KT80B-8/2-53 | 2 | 0,13/0,55 | 1,4/1,6 | 710/2890 | KT71B-2-53 | 2 | 0,55 | 1,4 | 2790 |
| | 4/1 | KT80B-8/2-53 | 2 | 0,13/0,55 | 1,4/1,6 | 710/2890 | KT71B-2-53 | 2 | 0,55 | 1,4 | 2790 |
| M732, M740 | 2/1 | KT80B-8/2-53 | 2 | 0,13/0,55 | 1,4/1,6 | 710/2890 | KT71B-2-53 | 2 | 0,55 | 1,4 | 2790 |
| | 4/1 | KT90S-8/2 | 2 | 0,18/0,75 | 1,4/1,9 | 680/2800 | KT80A-2 | 2 | 0,75 | 2,0 | 2820 |
| M750 | 2/1 | KT80B-8/2-53 | 2 | 0,13/0,55 | 1,4/1,6 | 710/2890 | KT71B-2-53 | 2 | 0,55 | 1,4 | 2790 |